



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



OMNI FIT™ Standard Connectors

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable		
Cable Size		1 1/4		
Cable Type		Foam Dielectric	Ultraflexible	Radiating
Model Series		UCF114-50 Series	LCFS114-50 Series	RCF114-50 Series
Connector Interface		7-16		
Connector Type		OMNI FIT™ Standard		
Sealing Method		O-ring		
Gender		Female		

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50		
3rd Order IM Product @ 2x20 Watts	dBc	-159 typical		
Maximum Frequency	GHz	3.6		
VSWR, Return Loss	VSWR (dB)	0 < f ≤ 1.0 GHz: 1.03 (36.6) 1.0 < f ≤ 2.7 GHz: 1.05 (32.3) 2.7 < f ≤ 3.6 GHz: 1.08 (28.3)		

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver		
Length	mm (in)	61 (2)		
Outer Diameter	mm (in)	49 (2)		
Weight	kg (lb)	0 (1)		
Inner Contact Attachment		Spring Finger		
Outer Contact Attachment		Spring C-Ring		




ACCESSORIES

Wrench size front	mm (in)	Open end wrench 45 (1-3/4)
Wrench size rear	mm (in)	Open end wrench 45 (1-3/4)
Poly Hook Spanner	mm (in)	PHS 60-90-5 Ø 60-90 (2.3-3.5) Pin 5 (0.2)

TESTING AND ENVIRONMENTAL

Waterproof Level		IP68
-------------------------	--	------



External Document Links

[Application Note](#)

[Installation Instruction](#)

Notes