



The set consists of a hot dip galvanized universal clamp and a rubber clamp lining for FLEXWELL® Elliptical Waveguide ES46

FEATURES / BENEFITS

Easy waveguide installation

- The universal clamp with clamp lining is used for proper and secure installation of elliptical waveguides
- A suitable rubber inlet is included



Technical features

GENERAL SPECIFICATIONS

| | | |
|------------------------|--|----------------------------------|
| Product Line | | Elliptical Waveguide Accessories |
| Product Type | | Hanger |
| Hanger Type | | Basic clamp with clamp lining |
| Transmission Line Type | | ES46 ESP46 |

MECHANICAL SPECIFICATIONS

| | | |
|----------------------------------|--|--|
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Clamp: Hot dip galvanized steel Clamp Lining: EPDM rubber |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|------------------|--|----|
| Package Quantity | | 10 |
|------------------|--|----|

[External Document Links](#)

[Notes](#)