Hangers for the installation of HELIFLEX® cables on different supporting profiles. Cable Clamp and Extended Counterbed hot-galvanized steel Screw: stainless steel.

FEATURES / BENEFITS



picture shows the 1L4 version for illustration purpose only

Technical features

GENERAL SPECIFICATIONS

| Product Line | Coaxial Cable Accessories |
|------------------------|---------------------------------|
| Product Type | Hanger |
| Hanger Type | Anchor bar 18-22mm (0.71-0.87") |
| Transmission Line Type | HCA300 |
| Cable Type | Air Dielectric |

MECHANICAL SPECIFICATIONS

| Cable Size | | 3 |
|----------------------------------------|--------|--------------------------------------------------------------------------------------------------------|
| Material | | Cable Clamp : hot-dip galvanized Extended Counterbed : hot-dip galvanized Screw: Stainless steel |
| Recommended / Maximum Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4) |

TEMPERATURE SPECIFICATIONS

| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
|-----------------------|---------|-------------------------|
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| Package Quantity | | 1 |
|------------------|---------|---------------|
| Weight per piece | kg (lb) | 0.495 (1.091) |

External Document Links

Notes

Hangers for anchor bar 18-22 mm (0.71-0.87")

HCH-300-1C REV : C REV DATE : 07.April 2014 www.rfsworld.com