Double Multi block hanger support systems are designed for organizing bundled runs of coax cable.

Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

FEATURES / BENEFITS



MBH114-2-F for illustration purpose

Technical features

GENERAL SPECIFICATIONS		
Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		UCF78 LCF78
Color		Black
MECHANICAL SPECIFICATIONS		
Cable Size		7/8
Number of Cable / Waveguide Runs		2 per layer, 1 layer, 2 run
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adpter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	160 (6.30)
Height	mm (in)	85 (3.35)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1 (2.75 / 3.25)
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

MBH78-2-F REV : C REV DATE : 05.Apr.2017 www.rfsworld.com



Double Multi-block hanger one layer, with angle member adapter

PACKAGING INFORMATION

Package Quantity		10
Weight per piece	kg (lb)	0.21 (0.46)
Weight per kit	kg (lb)	2.15 (4.6)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	430 x 330 x 70 (16.93 x 12.99 x 2.76)



picture shows MBH114-6-F for illustration purpose

External Document Links

Installation Instruction

Notes

MBH78-2-FREV : CREV DATE : 05.Apr.2017www.rfsworld.com