



Clic Clamp, 1/2" ALF,RCF,RLK polyamide black, halogen free  
fire class UL94HB


**FEATURES / BENEFITS**

Safe and efficient installation of RADIAFLEX® cable with clic-clamps. Simple mounting by using wall plugs and screws. Simply push in by hand, clamp will grip and lock by applying slight pressure.



**Technical features**

<b>GENERAL SPECIFICATIONS</b>		
Product Line		Radiating Cable Accessories
Product Type		Hanger
Hanger Type		SFS clamp
Transmission Line Type		ALFU RLK* RCF12-50*A HCA12-50
Cable Type		Air Dielectric Radiating Cable
Color		Black
<b>MECHANICAL SPECIFICATIONS</b>		
Cable Size		1/2
Number of Cable / Waveguide Runs		1
Material		Polyamide
<b>TESTING AND ENVIRONMENTAL</b>		
Fire Class		UL94 HB
<b>TEMPERATURE SPECIFICATIONS</b>		
Installation Temperature	°C (°F)	-20 to 80 (-4 to 176 )
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )
<b>PACKAGING INFORMATION</b>		
Package Quantity		150



[External Document Links](#)

[Notes](#)